




Position	Qty.	Description	Single Price
	1	<p>CR 10-8 A-FJ-A-V HQQV</p>  <p>Note! Product picture may differ from actual product</p> <p>Product No.: 96501095 Vertical, non-self-priming, multistage, in-line, centrifugal pump for installation in pipe systems and mounting on a foundation.</p> <p>The pump has the following characteristics:</p> <ul style="list-style-type: none"> - Impellers and intermediate chambers are made of Stainless steel DIN W.-Nr. DIN W.-Nr. 1.4301. - Pump head and base are made of Cast iron. - The shaft seal has assembly length according to EN 12756. - Power transmission is via cast iron split coupling. - Pipework connection is via DIN flanges. <p>The motor is a 3-phase AC motor.</p> <p>Liquid: Liquid temperature range: -20 .. 90 °C Density: 1000 kg/m³</p> <p>Technical: Speed for pump data: 2902 rpm Rated flow: 10 m³/h Rated head: 64.8 m Shaft seal: HQQV Approvals on nameplate: CE Curve tolerance: ISO 9906 Annex A</p> <p>Materials: Pump housing: Cast iron EN-JL1030 ASTM A48-30 B Impeller: Stainless steel DIN W.-Nr. 1.4301 AISI 304</p> <p>Installation: Maximum ambient temperature: 60 °C Max pressure at stated temp: 16 bar / 90 °C 16 bar / -20 °C Flange standard: DIN Pipe connection: DN 40 Pressure stage: PN 16</p>	Price on request



Company name: Grundfos Vietnam
Created by: Hoang Tuan Viet
Phone: +84 0982262111
Fax: Email: vietth@grundfos.com
Date: 11/02/2010

Position	Qty.	Description	Single Price
		Flange size for motor: FT130 Electrical data: Motor type: 100LC Efficiency class: 1 Number of poles: 2 Rated power - P2: 3 kW Power (P2) required by pump: 3 kW Mains frequency: 50 Hz Rated voltage: 3 x 220-240 D / 380-415 Y V Rated current: 11 / 6.3 A Starting current: 840-920 % Cos phi - power factor: 0,87-0,82 Rated speed: 2900-2920 rpm Enclosure class (IEC 34-5): 55 Insulation class (IEC 85): F Others: Net weight: 56 kg Gross weight: 60 kg Shipping volume: 0.12 m3	

Description	Value
Product name:	CR 10-8 A-FJ-A-V HQQV
Product No:	96501095
EAN number:	5700396215259
Price:	On request
Technical:	
Speed for pump data:	2902 rpm
Rated flow:	10 m ³ /h
Rated head:	64.8 m
Impellers:	08
Shaft seal:	HQQV
Approvals on nameplate:	CE
Curve tolerance:	ISO 9906 Annex A
Stages:	08
Pump version:	A
Model:	A
Materials:	
Pump housing:	Cast iron EN-JL1030
	ASTM A48-30 B
Impeller:	Stainless steel DIN W.-Nr. 1.4301 AISI 304
Material code:	A
Code for rubber:	V
Installation:	
Maximum ambient temperature:	60 °C
Max pressure at stated temp:	16 bar / 90 °C 16 bar / -20 °C
Flange standard:	DIN
Connect code:	FJ
Pipe connection:	DN 40
Pressure stage:	PN 16
Flange size for motor:	FT130
Liquid:	
Liquid temperature range:	-20 .. 90 °C
Density:	1000 kg/m ³
Electrical data:	
Motor type:	100LC
Efficiency class:	1
Number of poles:	2
Rated power - P2:	3 kW
Power (P2) required by pump:	3 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 220-240 D / 380-415 Y V
Rated current:	11 / 6.3 A
Starting current:	840-920 %
Cos phi - power factor:	0,87-0,82
Rated speed:	2900-2920 rpm
Enclosure class (IEC 34-5):	55
Insulation class (IEC 85):	F
Motor protec:	PTC
Motor No:	85D05510

Others:	
Net weight:	56 kg
Gross weight:	60 kg
Shipping volume:	0.12 m ³

